

04/19/02

L3 ANSWER 1 OF 1 WPIX COPYRIGHT 2002 DERWENT INFORMATION LTD
AN 1980-F4449C [25] WPIX Full-text
TI Noise free engine cylinder block cover - has moulded skeleton carrying stretched resilient layer, with holes for oil and air.
DC P86 Q51 Q52
IN ISHIHAMA, M
PA (NSMO) NISSAN MOTOR CO LTD
CYC 3
PI DE---2948572 A 19800612 (198025)*
GB---2037887 A 19800716 (198038) <--
FR---2443576 A 19800808 (198039)
GB---2037887 B 19821117 (198246) <--
PRAI 1978JP-0166824U 19781204
IC F01L-001-46; F02B-077-13; F02F-001-24; F02F-007-00; G10K-011-16
AB DE 2948572 A UPAB: 19930902 The cover for an engine cylinder block consists of a skeleton (1) with a thin material layer (2) stretched over it, to reduce noise and vibration. The skeleton has an open rectangular base with a flange (4) with bosses for clearance holes (5) for the securing bolts. This is integral with a number of arches to support the outer layer. The skeleton can be made as a casting using a wire or fibre reinforced plastics material. The outer layer can made of rubber or a rubber and nylon mixture. The structure can be formed to incorporate a lubrication oil connection and an air inlet connection.
FS GMPI
FA AB